



**Contatore Engineering
distribute a range of Rock breakers
for sale or hire.**

**The Socomec Rock breaker range is
available for light to heavy excavators.
The DMS Series for light to medium machines
and the MDO Series for the medium to heavy
excavator machines.**

**This leaflet focuses on the range
available in the DMS series, suited to
light to medium sized Excavators.**

- Suitable for 0.7 tonne to 14 tonne Excavator machines.
- Proven reliability in the field.
- Superior Noise and Vibration levels.
- Excellent after sales service and spare parts availability.
- Over 40 years of research and development / Socomec est. 1973.
- Low maintenance requirements

DMS



LIGHT RANGE SERIES DMS / HYDRAULIC ROCK BREAKER

The DMS Range of breakers is manufactured in one sole Monoblock structure without tie rods. This makes them more secure and reliable than traditional breakers, moreover, in case of break-down they are simple and economical to service. Two vulcanized polyurethane shells isolate the Monoblock from the metal case reducing noise level and vibrations.

MODEL		DMS 50	DMS 95/2	DMS 165	DMS 210	DMS 300	DMS 400	DMS 530	DMS 980
Energy	joule	120	240	330	500	700	900	1080	1600
Frequency	c/min	1200	1200	1200	1200	1100	900	900	900
Oil flow	L/min	17-25	27-40	35-50	40-55	50-70	70-95	80-110	100-130
Pressure	bar	120	120	120	120	120	120	120	130
Weight	kg	60	95	165	210	300	400	530	950
Tool Ø	mm	38	45	55	62	72	80	85	102
Height	mm	750	1000	1050	1200	1435	1455	1700	1830
Min. width	mm	125	130	165	190	205	225	235	280
Backpressure	bar	20/30	20/30	20/30	20/30	20/30	25	25	25
Excavator weight	t	0,7-1,2	1,2-1,8	2-3	2,8-4,5	4-7	6-8,5	8-11	10-14



ABN 39 119 888 505

www.contatoreengineering.com.au

97 Radium Street
Welshpool, WA, 6106

☎: (08) 9356 2725

☎: (08) 9351 8275

✉: admin@contatoreengineering.com.au

Engineering Excellence

Design | Machining | Fabrication | Hydraulics | Fitting

Mining | Civil | Custom Design & Prototypes | Earthmoving Attachments